



-----  
D.O.T. FLAMMABILITY CLASS.: NOT REGULATED      FLASH POINT: > 250 F PMCC  
LEL: Not Applicable  
EXTINGUISHING MEDIA: FOAM    CO2    DRY CHEMICAL    WATER FOG  
UNUSUAL FIRE AND EXPLOSION HAZARDS:  
Toxic gases may form when product burns.  
Closed containers may burst if exposed to extreme heat or fire.  
SPECIAL FIRE FIGHTING PROCEDURES:  
Cool exposed containers with water. Use self-contained breathing apparatus.  
-----

SECTION V    HEALTH HAZARD DATA

-----  
EFFECTS OF OVEREXPOSURE - ACUTE:  
Inhalation - Irritation of the respiratory tract.  
Skin and Eye Contact - Primary irritation.  
Contact - Causes skin irritation.  
Ingestion of large amounts could cause serious injury.  
EFFECTS OF OVEREXPOSURE - CHRONIC:  
Skin Contact - Prolonged or repeated exposure may cause dermatitis.  
Chronic lung conditions may be aggravated by exposure to high dust levels.  
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:  
None expected when used in accordance with Safe Handling and Use  
Information (Section VIII).  
PRIMARY ROUTE(S) OF ENTRY:    DERMAL      INHALATION      INGESTION  
EMERGENCY AND FIRST AID PROCEDURES :  
Inhalation - Remove to fresh air. Get medical help for any breathing  
difficulty.  
Eye Contact - Flush thoroughly with water. Call physician.  
Skin Contact - Wash with soap and water.  
Ingestion - Drink 1 or 2 glasses of water to dilute.  
DO NOT induce vomiting. Call physician.  
-----

SECTION VI    REACTIVITY DATA

-----  
STABILITY:    STABLE      HAZARDOUS POLYMERIZATION    WILL NOT OCCUR  
CONDITIONS TO AVOID: Elevated temperatures  
HAZARDOUS DECOMPOSITION PRODUCTS:  
Burning may produce carbon dioxide and carbon monoxide.  
INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.  
-----

SECTION VII    SPILL OR LEAK PROCEDURES

-----  
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:  
Flush with water. Absorb with sawdust or rags.  
WASTE DISPOSAL METHOD:  
Conventional procedures in compliance with local, state and federal  
regulations. Do not incinerate sealed containers.  
-----

SECTION VIII    SAFE HANDLING AND USE INFORMATION

-----  
RESPIRATORY PROTECTION:  
Use NIOSH approved respirator specified for protection against paint spray  
mist and sanding dust in restricted or confined areas.  
VENTILATION:  
Adequate to maintain working atmosphere below T.L.V. and L.E.L.  
(See Sect. II for ingredient data and concentrations). Mechanical exhaust  
may be required in confined areas.  
-----

PROTECTIVE GLOVES: Waterproof during repeated contact.  
EYE PROTECTION : Splash goggles or safety glasses with side shields.  
OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.  
HYGIENIC PRACTICES:  
Remove and wash clothing before reuse. Wash hands before eating, smoking  
or using the washroom.

---

SECTION IX SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS :

Avoid contact with eyes and prolonged contact with skin or breathing of  
spray mist or sanding dust.

Close container after each use. Keep out of reach of children. Do not  
take internally.

---

SECTION XX

---

HMIS (Hazardous Materials Identification System)(R) NPCA  
HMIS is a recognized workplace Hazard Communications System as required by  
OSHA (29 CFR 1910.1200). Information on establishing a compliant hazardous  
communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division  
5724 N. Pulaski Rd., Chicago, IL 60646  
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings;  
the contractor/employer has ultimate responsibility for HMIS rating where  
this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's  
as it depends on application technique and the workplace ventilation.  
Please read Sections II through IX of this MSDS before deciding on  
appropriate protective equipment and beginning work. There are codes  
available for this section which can be obtained from Labelmaster.

This product contains at least one toxic chemical listed in Section II  
that is subject to the reporting requirements of section 313 of the  
Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372.

---

DISCLAIMER

---

The information contained herein is presented in good faith and believed  
to be accurate as of the effective date shown above. This information is  
furnished without warranty of any kind. Employers should use this  
information only as a supplement to other information gathered by them and  
must make independent determination of suitability and completeness of  
information from all sources to assure proper use of these materials and  
the safety and health of employees. Any use of this data and information  
must be determined by the user to be in accordance with applicable federal,  
state and local laws and regulations.

WARNING: If you scrape, sand, or remove old paint, you may release lead  
dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS,  
SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO  
AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure.  
Clean up carefully with a HEPA vacuum and a wet mop. Before you start,  
find out how to protect yourself and your family by contacting the National  
Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).