

**Features**

- ▲ Studio Finishes™ Chalkboard paint (307) is a topcoat that turns any interior surface into a chalkboard
- ▲ Goes on easily and is washable
- ▲ Resists spattering during application
- ▲ Dries to a decorative finish that is extremely durable
- ▲ Is formulated to minimize lingering odors
- ▲ Soap and water clean-up
- ▲ Dries quickly

**General Description**

Studio Finishes™ Chalkboard paint (307) is acrylic-based and turns virtually any interior surface into a chalkboard.

**Recommended For:**

For interior use on previously painted surfaces. Use wherever a chalkboard finish is desired.

**Limitations:**

- Do not apply when air and surface temperatures are below 50° F (10° C)

**Product Information**

**Colors: —Standard:**  
Black

**—Tint Bases:**  
None

**—Special Colors:**  
None

**Certification:**  
Formulated without lead, mercury, or chromates.  
Very low in VOCs.

**Federal Specifications Generic Equivalent:**  
TT-P-2119

**Technical Assistance**  
Available through your local authorized independent Benjamin Moore® retailer. For the location of the retailer nearest you, call 1-800-826-2623, see [www.benjaminmoore.com](http://www.benjaminmoore.com), or consult your local Yellow Pages.

<b>Technical Data</b>	<b>Black</b>
Vehicle Type	100% Acrylic
Pigment Type <sup>◊</sup>	Titanium Dioxide
Volume Solids <sup>◊</sup>	40%
Theoretical Coverage At Recommended Film Thickness	100 – 110 Sq. Ft. per quart
Recommended Film Thickness – Wet – Dry	3.8 mils 1.4 mils
Dry Time @ 77° F — Set To Touch (25° C) @ 50% RH — To Handle — To Recoat — To Service	2 Hours 2 Hours 4 Hours 3 Days
Dries By	Evaporation, Coalescence
Viscosity <sup>◊</sup>	95 ± 2 KU
Flash Point (Seta)	None
60° Specular Gloss	Eggshell
Surface Temperature at application – Min. – Max.	50° F 90° F
Thin With	Clean Water
Clean Up Thinner	Clean Water
Weight Per Gallon <sup>◊</sup>	10.5 lbs.
Storage Temperature – Min. – Max.	40° F 90° F
Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 100 Grams/Liter. **</i>	

\*\* Contact Benjamin Moore & Co. for actual levels, which may or may not be substantially less than stated.  
<sup>◊</sup> Values given are for color shown; other colors may vary.

TDS307E

## Surface Preparation

Surfaces must be clean, dry and free of wax, grease, dust, mildew, water-soluble materials and scaling paint. Hard, glossy areas should be dulled with sandpaper to ensure proper adhesion.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## Primer/Finish Systems

Use the appropriate Benjamin Moore Fresh Start® primer if a primer is required. Follow label directions. For best results when significant color change is desired, tint the primer to the approximate base color.

For previously painted surfaces in good condition, apply one or two coats of this product. Otherwise, before and after filling in nail holes, cracks and other surface imperfections, spot prime with this product. When dry, apply one or two finish coats of Studio Finishes™ Chalkboard paint (307).

## Application

Stir thoroughly. Apply one or two coats. For best results, use a Benjamin Moore® custom-blended nylon/polyester brush, Benjamin Moore® roller, or a similar product. This product can also be sprayed. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 50°F (10°C).

## Thinning/Cleanup

Thinning is unnecessary, but if required to obtain desired application properties, a small amount of clean water may be added. Never add other paints or solvents. Wash painting tools in warm, soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

USE COMPLETELY OR DISPOSE OF PROPERLY. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary, consult your sanitation department or state-designated environmental agency for more information on disposal options.**

## Environmental, Health & Safety Information

**Use only with adequate ventilation.** Do not breathe spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves during application or sanding. A dust/particulate respirator approved by NIOSH should be worn when sanding or spraying. Close container after each use.

**FIRST AID:** If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, call physician immediately.

**IN CASE OF SPILL:** Absorb with inert material and dispose of as specified under "THINNING/CLEAN UP".

**KEEP OUT OF REACH OF CHILDREN**

**PROTECT FROM FREEZING**

**Material Safety Data Sheets available  
on request from your servicing retailer.**